

| Kód trysky | Otvor Ø | Uhol | Veľkosť kvapky | Veľkosť závitu | Farba O krížku | Prietok l/min a g/min 1 GPM = 3.785 LPM | | | | | | | | | | | |
|------------|------------|------|----------------|------------------------------|----------------|--|-------------------|-------------------|-------------------|--------------------|--------------------|--------------------|---------------------|---------------------|---------------------|---------------------|--|
| | | | | | | 30 BAR 435 PSI | 40 BAR 580 PSI | 50 BAR 725 PSI | 60 BAR 970 PSI | 70 BAR 1000 PSI | 80 BAR 1160 PSI | 90 BAR 1305 PSI | 100 BAR 1450 PSI | 110 BAR 1595 PSI | 120 BAR 1740 PSI | 130 BAR 1885 PSI | |
| NM10BH-M | 0.10 mm | 45° | 3 µ | M5 UNC 10-24 UNC 12-24 | žltá | .017 | .022 | .027 | .030 | .039 | .042 | .044 | .045 | .047 | .049 | | |
| NM10BH-U1 | 0.004" | 45° | 3 µ | M5 UNC 10-24 UNC 12-24 | čierna | .005 | .006 | .007 | .008 | .010 | .011 | .012 | .012 | .012 | .013 | | |
| NM10BH-U2 | 0.004" | 45° | 3 µ | M5 UNC 10-24 UNC 12-24 | modrá | .005 | .006 | .007 | .008 | .010 | .011 | .012 | .012 | .012 | .013 | | |
| NM15BH-M | 0.15 mm | 55° | 5 µ | M5 UNC 10-24 UNC 12-24 | žltá | .024 | .038 | .047 | .050 | .058 | .064 | .068 | .070 | .072 | .075 | | |
| NM15BH-U1 | 0.006" | 55° | 5 µ | M5 UNC 10-24 UNC 12-24 | čierna | .006 | .010 | .012 | .013 | .015 | .017 | .018 | .018 | .019 | .020 | | |
| NM15BH-U2 | 0.006" | 55° | 5 µ | M5 UNC 10-24 UNC 12-24 | modrá | .006 | .010 | .012 | .013 | .015 | .017 | .018 | .018 | .019 | .020 | | |
| NM20BH-M | 0.20 mm | 70° | 6 µ | M5 UNC 10-24 UNC 12-24 | žltá | .041 | .057 | .071 | .075 | .081 | .085 | .091 | .093 | .097 | .102 | | |
| NM20BH-U1 | 0.008" | 70° | 6 µ | M5 UNC 10-24 UNC 12-24 | čierna | .011 | .015 | .017 | .020 | .021 | .022 | .024 | .025 | .025 | .027 | | |
| NM20BH-U2 | 0.008" | 70° | 6 µ | M5 UNC 10-24 UNC 12-24 | modrá | .011 | .015 | .017 | .020 | .021 | .022 | .024 | .025 | .025 | .027 | | |
| NM30BH-M | 0.30 mm | 85° | 8 µ | M5 UNC 10-24 UNC 12-24 | žltá | .070 | .082 | .102 | .105 | .116 | .122 | .132 | .140 | .146 | .150 | | |
| NM30BH-U1 | 0.012" | 85° | 8 µ | M5 UNC 10-24 UNC 12-24 | čierna | .018 | .022 | .024 | .027 | .031 | .032 | .035 | .037 | .038 | .040 | | |
| NM30BH-U2 | 0.012" | 85° | 8 µ | M5 UNC 10-24 UNC 12-24 | modrá | .018 | .022 | .024 | .027 | .031 | .032 | .035 | .037 | .038 | .040 | | |
| NM40BH-M | 0.40 mm | 90° | 11 µ | M5 UNC 10-24 UNC 12-24 | žltá | .094 | .116 | .142 | .150 | .159 | .169 | .185 | .190 | .197 | .209 | | |
| NM40BH-U1 | 0.016" | 90° | 11 µ | M5 UNC 10-24 UNC 12-24 | čierna | .025 | .031 | .037 | .040 | .042 | .045 | .050 | .050 | .052 | .055 | | |
| NM40BH-U2 | 0.016" | 90° | 11 µ | M5 UNC 10-24 UNC 12-24 | modrá | .025 | .031 | .037 | .040 | .042 | .045 | .050 | .050 | .052 | .055 | | |
| NM50BH-M | 0.50 mm | 95° | 13 µ | M5 UNC 10-24 UNC 12-24 | žltá | .117 | .136 | .160 | .190 | .195 | .209 | .228 | .235 | .240 | .250 | | |
| NM50BH-U1 | 0.020" | 95° | 13 µ | M5 UNC 10-24 UNC 12-24 | čierna | .031 | .036 | .042 | .050 | .052 | .055 | .060 | .062 | .064 | .066 | | |
| NM50BH-U2 | 0.020" | 95° | 13 µ | M5 UNC 10-24 UNC 12-24 | modrá | .031 | .036 | .042 | .050 | .052 | .055 | .060 | .062 | .064 | .066 | | |
| NM60BH-M | 0.60 mm | 95° | 17 µ | M5 UNC 10-24 UNC 12-24 | žltá | .135 | .162 | .180 | .210 | .228 | .241 | .255 | .275 | .285 | .300 | | |
| NM60BH-U1 | 0.024" | 95° | 17 µ | M5 UNC 10-24 UNC 12-24 | čierna | .036 | .043 | .047 | .052 | .060 | .064 | .067 | .072 | .075 | .079 | | |
| NM60BH-U2 | 0.024" | 95° | 17 µ | M5 UNC 10-24 UNC 12-24 | modrá | .036 | .043 | .047 | .052 | .060 | .064 | .067 | .072 | .075 | .079 | | |
| NM70BH-M | 0.70 mm | 100° | 20 µ | M5 UNC 10-24 UNC 12-24 | žltá | .161 | .184 | .209 | .240 | .256 | .274 | .294 | .305 | .315 | .330 | | |
| NM70BH-U1 | 0.028" | 100° | 20 µ | M5 UNC 10-24 UNC 12-24 | čierna | .042 | .049 | .055 | .060 | .068 | .072 | .077 | .080 | .083 | .087 | | |
| NM70BH-U2 | 0.028" | 100° | 20 µ | M5 UNC 10-24 UNC 12-24 | modrá | .042 | .049 | .055 | .060 | .068 | .072 | .077 | .080 | .083 | .087 | | |

Materiál trysiek je: nehrdzavejúci ocel typu 316, veľkosť otvoru je laserom označené na tele trysky. *Merané pri 70bar/1000PSI